



WMC30

FONTANELLA	FOUNTAIN	FONTAINES	
Fontanella refrigerante con scambio diretto senza accumulo	Drinking water fountain with direct cooling system without tank	Fontaine réfrigérante avec système de refroidissement sans réservoir	
Sistema di raffreddamento: sistema diretto esclusivo Frigeria senza accumulo	Cooling system: exclusive Frigeria direct cooling system without tank	Système de refroidissement: système direct exclusif Frigeria sans réservoir	
Sistema di erogazione: a pulsante	Dispensing system: push botton	Système de distribution: poussoir	
Produzione d'acqua fredda	Delivery of cold water	Débit d'eau froide	25 ÷ 32 l/h
Assorbimento	Absorption	Absorption	102 W
Potenza frigorifera	Cooling power	Puissance de réfrigération	282 W
Pressione di esercizio	Operating pressure	Pression de fonctionnement	3 bar
Alimentazione	Power supply	Alimentation	230 V – 50 Hz
Compressore	Compressor	Compresseur	1/6 HP
Gas R134a	Gas R134a	Gaz R134a	200 g
Rumorosità	Noise	Bruit	<67 db.
Dimensioni (mm)	Dimensions (mm)	Dimensions (mm)	380 x 320 x 580
Peso	Weight	Poids	28 kg
Pannelli	Panels	Panneaux	Skinplated or stainless steel
Lavello	Sink	Évier	Stainless steel AISI 304
Voltaggi speciali	Special voltages	Voltages spéciaux	Upon request
Allestimenti personalizzati	Personalized equipment	È quipements personnalisés	Upon request



WMC45

FONTANELLA	FOUNTAIN	FONTAINES	
Fontanella refrigerante con scambio diretto senza accumulo	Drinking water fountain with direct cooling system without tank	Fontaine réfrigérante avec système de refroidissement sans réservoir	
Sistema di raffreddamento: sistema diretto esclusivo Frigeria senza accumulo	Cooling system: exclusive Frigeria direct cooling system without tank	Système de refroidissement: système direct exclusif Frigeria sans réservoir	
Sistema di erogazione: a pulsante	Dispensing system: push botton	Système de distribution: poussoir	
Produzione d'acqua fredda	Delivery of cold water	Débit d'eau froide	45 ÷ 50 l/h
Assorbimento	Absorption	Absorption	151 W
Potenza frigorifera	Cooling power	Puissance de réfrigération	422 W
Pressione di esercizio	Operating pressure	Pression de fonctionnement	3 bar
Alimentazione	Power supply	Alimentation	230 V – 50 Hz
Compressore	Compressor	Compresseur	1/5 HP
Gas R134a	Gas R134a	Gaz R134a	200 g
Rumorosità	Noise	Bruit	<67 db.
Dimensioni (mm)	Dimensions (mm)	Dimensions (mm)	380 x 320 x 580
Peso	Weight	Poids	30 kg
Pannelli	Panels	Panneaux	Skinplated or stainless steel
Lavello	Sink	Évier	Stainless steel AISI 304
Voltaggi speciali	Special voltages	Voltages spéciaux	Upon request
Allestimenti personalizzati	Personalized equipment	É quipements personnalisés	Upon request